



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

### 1 Identification

- **Product identifier**
- **Trade name:** H500 2K HARDENER FAST
- **Article number:** H500
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3    H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1    H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2    H351 Suspected of causing cancer.



GHS07

Acute Tox. 4    H312 Harmful in contact with skin.

Acute Tox. 4    H332 Harmful if inhaled.

Skin Irrit. 2    H315 Causes skin irritation.

Eye Irrit. 2A    H319 Causes serious eye irritation.

STOT SE 3    H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** *Danger***· Hazard-determining components of labeling:**

Homopolymer of hexamethylene diisocyanate  
Isophorone Diisocyanate homopolymer  
xylene

**· Hazard statements**

Flammable liquid and vapor.  
Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
May cause respiratory irritation.

**· Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
[In case of inadequate ventilation] wear respiratory protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
If experiencing respiratory symptoms: Call a poison center/doctor.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

|            |                                           |           |
|------------|-------------------------------------------|-----------|
| 28182-81-2 | Homopolymer of hexamethylene diisocyanate | >25-≤50%  |
| 1330-20-7  | xylene                                    | >25-≤50%  |
| 123-86-4   | n-butyl acetate                           | >10-≤25%  |
| 53880-05-0 | Isophorone Diisocyanate homopolymer       | >2.5-≤10% |
| 108-65-6   | 2-methoxy-1-methylethyl acetate           | >2.5-≤10% |
| 100-41-4   | ethylbenzene                              | ≤2.5%     |

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 4)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 3)

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

**PAC-1:**

|            |                                           |                       |
|------------|-------------------------------------------|-----------------------|
| 28182-81-2 | Homopolymer of hexamethylene diisocyanate | 7.8 mg/m <sup>3</sup> |
| 1330-20-7  | xylene                                    | 130 ppm               |
| 123-86-4   | n-butyl acetate                           | 5 ppm                 |
| 108-65-6   | 2-methoxy-1-methylethyl acetate           | 50 ppm                |
| 100-41-4   | ethylbenzene                              | 33 ppm                |
| 822-06-0   | hexamethylene-di-isocyanate               | 0.018 ppm             |
| 77-58-7    | dibutyltin dilaurate                      | 1.1 mg/m <sup>3</sup> |

(Contd. on page 5)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 4)

|                 |                                                         |                       |
|-----------------|---------------------------------------------------------|-----------------------|
| 4098-71-9       | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 0.02 ppm              |
| <b>· PAC-2:</b> |                                                         |                       |
| 28182-81-2      | Homopolymer of hexamethylene diisocyanate               | 86 mg/m <sup>3</sup>  |
| 1330-20-7       | xylene                                                  | 920* ppm              |
| 123-86-4        | n-butyl acetate                                         | 200 ppm               |
| 108-65-6        | 2-methoxy-1-methylethyl acetate                         | 1,000 ppm             |
| 100-41-4        | ethylbenzene                                            | 1100* ppm             |
| 822-06-0        | hexamethylene-di-isocyanate                             | 0.2 ppm               |
| 77-58-7         | dibutyltin dilaurate                                    | 8 mg/m <sup>3</sup>   |
| 4098-71-9       | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 0.14 ppm              |
| <b>· PAC-3:</b> |                                                         |                       |
| 28182-81-2      | Homopolymer of hexamethylene diisocyanate               | 510 mg/m <sup>3</sup> |
| 1330-20-7       | xylene                                                  | 2500* ppm             |
| 123-86-4        | n-butyl acetate                                         | 3000* ppm             |
| 108-65-6        | 2-methoxy-1-methylethyl acetate                         | 5000* ppm             |
| 100-41-4        | ethylbenzene                                            | 1800* ppm             |
| 822-06-0        | hexamethylene-di-isocyanate                             | 3 ppm                 |
| 77-58-7         | dibutyltin dilaurate                                    | 48 mg/m <sup>3</sup>  |
| 4098-71-9       | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | 0.6 ppm               |

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 6)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 5)

**· Control parameters****· Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

**1330-20-7 xylene**

|     |                                                                                                              |
|-----|--------------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                             |
| REL | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |

**123-86-4 n-butyl acetate**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 710 mg/m <sup>3</sup> , 150 ppm                                                      |
| REL | Short-term value: 950 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 710 mg/m <sup>3</sup> , 150 ppm |
| TLV | Short-term value: 712 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 238 mg/m <sup>3</sup> , 50 ppm  |

**108-65-6 2-methoxy-1-methylethyl acetate**

|      |                         |
|------|-------------------------|
| WEEL | Long-term value: 50 ppm |
|------|-------------------------|

**100-41-4 ethylbenzene**

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI                                                 |

**· Ingredients with biological limit values:****1330-20-7 xylene**

|     |                                                                                              |
|-----|----------------------------------------------------------------------------------------------|
| BEI | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----|----------------------------------------------------------------------------------------------|

**100-41-4 ethylbenzene**

|     |                                                                                                                                                                           |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BEI | 0.7 g/g creatinine<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| -   | Medium: end-exhaled air<br>Time: not critical<br>Parameter: Ethyl benzene (semi-quantitative)                                                                             |

(Contd. on page 7)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 6)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing.
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes and skin.
- **Breathing equipment:**
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
  - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - Form:** Fluid
  - Color:** According to product description
  - Odor:** Characteristic

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 7)

|                                                                                                                          |                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|
| · <b>Odor threshold:</b>                                                                                                 | Not determined.                                                                                      |
| · <b>pH-value:</b>                                                                                                       | Not determined.                                                                                      |
| · <b>Change in condition</b><br><b>Melting point/Melting range:</b><br><b>Boiling point/Boiling range:</b>               | Undetermined.<br>124 °C (255.2 °F)                                                                   |
| · <b>Flash point:</b>                                                                                                    | 25 °C (77 °F)                                                                                        |
| · <b>Flammability (solid, gaseous):</b>                                                                                  | Not applicable.                                                                                      |
| · <b>Ignition temperature:</b>                                                                                           | 370 °C (698 °F)                                                                                      |
| · <b>Decomposition temperature:</b>                                                                                      | Not determined.                                                                                      |
| · <b>Auto igniting:</b>                                                                                                  | Product is not selfigniting.                                                                         |
| · <b>Danger of explosion:</b>                                                                                            | Product is not explosive. However, formation of explosive air/vapor mixtures are possible.           |
| · <b>Explosion limits:</b><br><b>Lower:</b><br><b>Upper:</b>                                                             | 1.1 Vol %<br>7.5 Vol %                                                                               |
| · <b>Vapor pressure at 20 °C (68 °F):</b>                                                                                | 10.7 hPa (8 mm Hg)                                                                                   |
| · <b>Density at 20 °C (68 °F):</b><br>· <b>Relative density</b><br>· <b>Vapor density</b><br>· <b>Evaporation rate</b>   | 1.02697 g/cm <sup>3</sup> (8.57006 lbs/gal)<br>Not determined.<br>Not determined.<br>Not determined. |
| · <b>Solubility in / Miscibility with Water:</b>                                                                         | Not miscible or difficult to mix.                                                                    |
| · <b>Partition coefficient (n-octanol/water):</b>                                                                        | Not determined.                                                                                      |
| · <b>Viscosity:</b><br><b>Dynamic:</b><br><b>Kinematic:</b>                                                              | Not determined.<br>Not determined.                                                                   |
| · <b>Solvent content:</b><br><b>Organic solvents:</b><br><b>Coating VOC content:</b><br><br><b>Material VOC content:</b> | 50.1 %<br>50.07 %<br>514.2 g/l / 4.29 lb/gl<br>514.2 g/l / 4.29 lb/gl                                |
| <b>Solids content:</b><br>· <b>Other information</b>                                                                     | 50.7 %<br>No further relevant information available.                                                 |

US  
(Contd. on page 9)





## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 8)

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through inhalation.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |              |    |
|-----------|--------------|----|
| 1330-20-7 | xylene       | 3  |
| 100-41-4  | ethylbenzene | 2B |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

(Contd. on page 10)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 9)

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                                                                     |                     |
|-------------------------------------------------------------------------------------|---------------------|
| · <b>UN-Number</b>                                                                  |                     |
| · <b>DOT, ADR, IMDG, IATA</b>                                                       | UN1263              |
| · <b>UN proper shipping name</b>                                                    |                     |
| · <b>DOT</b>                                                                        | Paint               |
| · <b>ADR</b>                                                                        | 1263 Paint          |
| · <b>IMDG, IATA</b>                                                                 | PAINT               |
| · <b>Transport hazard class(es)</b>                                                 |                     |
| · <b>DOT</b>                                                                        |                     |
|  |                     |
| · <b>Class</b>                                                                      | 3 Flammable liquids |

(Contd. on page 11)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 10)

|                                                                                   |                                                                                                                  |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>ADR, IMDG, IATA</b>                                                          |                                                                                                                  |
|  |                                                                                                                  |
| · <b>Class</b>                                                                    | 3 Flammable liquids                                                                                              |
| · <b>Label</b>                                                                    | 3                                                                                                                |
| · <b>Packing group</b>                                                            |                                                                                                                  |
| · <b>DOT, ADR, IMDG, IATA</b>                                                     | III                                                                                                              |
| · <b>Environmental hazards:</b>                                                   |                                                                                                                  |
| · <b>Marine pollutant:</b>                                                        | No                                                                                                               |
| · <b>Special precautions for user</b>                                             | Warning: Flammable liquids                                                                                       |
| · <b>Danger code (Kemler):</b>                                                    | 30                                                                                                               |
| · <b>EMS Number:</b>                                                              | F-E, S-E                                                                                                         |
| · <b>Stowage Category</b>                                                         | A                                                                                                                |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>  | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                        |                                                                                                                  |
| · <b>DOT</b>                                                                      |                                                                                                                  |
| · <b>Quantity limitations</b>                                                     | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L                                                |
| · <b>ADR</b>                                                                      |                                                                                                                  |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>IMDG</b>                                                                     |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                  | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                 | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>                                                   | UN 1263 PAINT, 3, III                                                                                            |

US

(Contd. on page 12)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 11)

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

**· Section 355 (extremely hazardous substances):**

|           |                                                         |
|-----------|---------------------------------------------------------|
| 4098-71-9 | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate |
|-----------|---------------------------------------------------------|

**· Section 313 (Specific toxic chemical listings):**

|           |        |
|-----------|--------|
| 1330-20-7 | xylene |
|-----------|--------|

|          |              |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

|          |                             |
|----------|-----------------------------|
| 822-06-0 | hexamethylene-di-isocyanate |
|----------|-----------------------------|

|           |                                                         |
|-----------|---------------------------------------------------------|
| 4098-71-9 | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate |
|-----------|---------------------------------------------------------|

**· TSCA (Toxic Substances Control Act):**

|                             |  |
|-----------------------------|--|
| All ingredients are listed. |  |
|-----------------------------|--|

**· TSCA new (21st Century Act) (Substances not listed)**

|            |                                     |
|------------|-------------------------------------|
| 53880-05-0 | Isophorone Diisocyanate homopolymer |
|------------|-------------------------------------|

**· Proposition 65****· Chemicals known to cause cancer:**

|          |              |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

**· Chemicals known to cause reproductive toxicity for females:**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

**· Chemicals known to cause reproductive toxicity for males:**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

**· Chemicals known to cause developmental toxicity:**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

**· Carcinogenic categories****· EPA (Environmental Protection Agency)**

|           |        |   |
|-----------|--------|---|
| 1330-20-7 | xylene | I |
|-----------|--------|---|

|          |              |   |
|----------|--------------|---|
| 100-41-4 | ethylbenzene | D |
|----------|--------------|---|

**· TLV (Threshold Limit Value established by ACGIH)**

|           |        |    |
|-----------|--------|----|
| 1330-20-7 | xylene | A4 |
|-----------|--------|----|

|          |              |    |
|----------|--------------|----|
| 100-41-4 | ethylbenzene | A3 |
|----------|--------------|----|

|         |                      |    |
|---------|----------------------|----|
| 77-58-7 | dibutyltin dilaurate | A4 |
|---------|----------------------|----|

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

|                                    |  |
|------------------------------------|--|
| None of the ingredients is listed. |  |
|------------------------------------|--|

**· GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 13)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 12)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** *Danger***· Hazard-determining components of labeling:**

Homopolymer of hexamethylene diisocyanate  
Isophorone Diisocyanate homopolymer  
xylene

**· Hazard statements**

Flammable liquid and vapor.  
Harmful in contact with skin or if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing cancer.  
May cause respiratory irritation.

**· Precautionary statements**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
[In case of inadequate ventilation] wear respiratory protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
If experiencing respiratory symptoms: Call a poison center/doctor.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 14)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 07/16/2018

Reviewed on 06/04/2018

**Trade name: H500 2K HARDENER FAST**

(Contd. of page 13)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** Ms. Topaljikian

• **Date of preparation / last revision** 07/16/2018 / -

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3