



Safety Data Sheet acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

1 Identification

- **Product identifier**
- **Trade name:** GP587 HOT ROD SATIN BLACK
- **Article number:** GP587
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
4725 S Camp Kearns Road
Kearns, UT 84118
USA
www.lusidtechnologies.com
- **Information department:** Product safety department
- **Emergency telephone number:**
24 Hrs Emergency Contact:
INFOTRAC
1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

acetone
Solvent naphtha (petroleum), light arom.
n-butyl acetate
2-butanone oxime

· Hazard statements

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	25-50%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
1330-20-7	xylene	10-25%
64742-49-0	Naphtha (petroleum), hydrotreated light	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
110-43-0	heptan-2-one	≤2.5%
112926-00-8	Precipitated silica (Silica-Amorphous)	≤2.5%
107-87-9	pentan-2-one	≤2.5%
1333-86-4	Carbon black	≤2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤2.5%
96-29-7	2-butanone oxime	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 4)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
110-43-0	heptan-2-one	150 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m ³
9002-88-4	Polyethylene low density	16 mg/m ³
107-87-9	pentan-2-one	150 ppm
1333-86-4	Carbon black	9 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm
96-29-7	2-butanone oxime	30 ppm
8052-41-3	Stoddard solvent	300 mg/m ³
108-83-8	2,6-dimethylheptan-4-one	75 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
100-41-4	ethylbenzene	33 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
122-99-6	2-Phenoxyethanol	1.5 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	30 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: **GP587 HOT ROD SATIN BLACK**

(Contd. of page 4)

149-57-5	2-ethylhexanoic acid	15 mg/m ³
PAC-2:		
67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
110-43-0	heptan-2-one	670 ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m ³
9002-88-4	Polyethylene low density	170 mg/m ³
107-87-9	pentan-2-one	830 ppm
1333-86-4	Carbon black	99 mg/m ³
95-63-6	1,2,4-trimethylbenzene	360 ppm
96-29-7	2-butanone oxime	56 ppm
8052-41-3	Stoddard solvent	1,800 mg/m ³
108-83-8	2,6-dimethylheptan-4-one	330 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
100-41-4	ethylbenzene	1100* ppm
77-58-7	dibutyltin dilaurate	8 mg/m ³
122-99-6	2-Phenoxyethanol	16 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	33 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
149-57-5	2-ethylhexanoic acid	99 mg/m ³

PAC-3:		
67-64-1	acetone	5700* ppm
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
110-43-0	heptan-2-one	4000* ppm
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m ³
9002-88-4	Polyethylene low density	1,000 mg/m ³
107-87-9	pentan-2-one	5000* ppm
1333-86-4	Carbon black	590 mg/m ³
95-63-6	1,2,4-trimethylbenzene	480 ppm
96-29-7	2-butanone oxime	250 ppm
8052-41-3	Stoddard solvent	29500** mg/m ³
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
100-41-4	ethylbenzene	1800* ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³
122-99-6	2-Phenoxyethanol	97 ppm
112-34-5	2-(2-butoxyethoxy)ethanol	200 ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 5)

149-57-5 2-ethylhexanoic acid

590 mg/m³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 At this time, the other constituents have no known exposure limits.

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
	BEI

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm
	Long-term value: 434 mg/m ³ , 100 ppm
	BEI

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 6)

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm
REL Long-term value: 465 mg/m³, 100 ppm
TLV Long-term value: 233 mg/m³, 50 ppm

112926-00-8 Precipitated silica (Silica-Amorphous)

PEL 20mppcf or 80mg/m³ /%SiO₂
REL Long-term value: 6 mg/m³
See Pocket Guide App. C
TLV TLV withdrawn

107-87-9 pentan-2-one

PEL Long-term value: 700 mg/m³, 200 ppm
REL Long-term value: 530 mg/m³, 150 ppm
TLV Short-term value: 529 mg/m³, 150 ppm

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³
REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps. A+C
TLV Long-term value: 3* mg/m³
*inhalable fraction

96-29-7 2-butanone oxime

WEEL Long-term value: 10 ppm
DSEN

Ingredients with biological limit values:**67-64-1 acetone**

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 7)

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Color:	Black
Odor:	Product specific
Odor threshold:	Not determined.

pH-value: Not determined (pH N/A in solvent coatings)

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)

Flash point: <-18 °C (<-0.4 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 465 °C (869 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.

Explosion limits:

Lower: 1.1 Vol %

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: **GP587 HOT ROD SATIN BLACK**

(Contd. of page 8)

Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
· Density at 20 °C (68 °F):	1.0187 g/cm ³ (8.5011 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	51.5 %
VOC content:	23.71 %
	408.4 g/l / 3.41 lb/gal
· Solids content:	37.4 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 9)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
9002-88-4	Polyethylene low density	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B
136-52-7	cobalt(II) 2-ethylhexanoate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Not hazardous for water.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA**

UN1263

(Contd. on page 11)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 10)

· UN proper shipping name

· DOT

· IMDG, IATA

Paint

PAINT

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, IMDG, IATA

II

· Environmental hazards:

Not applicable.

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

33

· EMS Number:

F-E, S-E

· Stowage Category

B

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 12)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 11)

Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
95-63-6	1,2,4-trimethylbenzene
100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate
122-99-6	2-Phenoxyethanol
112-34-5	2-(2-butoxyethoxy)ethanol

TSCA (Toxic Substances Control Act):

67-64-1	acetone	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
1330-20-7	xylene	ACTIVE
123-86-4	n-butyl acetate	ACTIVE
110-43-0	heptan-2-one	ACTIVE
9002-88-4	Polyethylene low density	ACTIVE
107-87-9	pentan-2-one	ACTIVE
1333-86-4	Carbon black	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
95-63-6	1,2,4-trimethylbenzene	ACTIVE
96-29-7	2-butanone oxime	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
108-83-8	2,6-dimethylheptan-4-one	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
34590-94-8	Dipropylene glycol monomethyl ether	ACTIVE
100-41-4	ethylbenzene	ACTIVE
136-52-7	cobalt(II) 2-ethylhexanoate	ACTIVE
77-58-7	dibutyltin dilaurate	ACTIVE
122-99-6	2-Phenoxyethanol	ACTIVE
112-34-5	2-(2-butoxyethoxy)ethanol	ACTIVE
149-57-5	2-ethylhexanoic acid	ACTIVE

Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
136-52-7	cobalt(II) 2-ethylhexanoate

Proposition 65
Chemicals known to cause cancer:

1333-86-4	Carbon black
100-41-4	ethylbenzene

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 12)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
1330-20-7	xylene	I
95-63-6	1,2,4-trimethylbenzene	II
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetone

Solvent naphtha (petroleum), light arom.

n-butyl acetate

2-butanone oxime

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 14)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/17/2019

Reviewed on 04/17/2019

Trade name: GP587 HOT ROD SATIN BLACK

(Contd. of page 13)

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Specific treatment (see on this label).**Take off contaminated clothing and wash it before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Wash contaminated clothing before reuse.**In case of fire: Use for extinction: CO₂, powder or water spray.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***• National regulations:****• Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.***• Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***• Department issuing SDS:** Environment protection department.**• Contact:** Product Safety Dept.**• Date of preparation / last revision** 04/17/2019 / -**• Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3